

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 September 2004 (16.09.2004)

PCT

(10) International Publication Number
WO 2004/079157 A1

(51) International Patent Classification⁷: **E21B 43/10**

(21) International Application Number:
PCT/US2004/002905

(22) International Filing Date: 2 February 2004 (02.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/450,899 28 February 2003 (28.02.2003) EP

(71) Applicant: **BAKER HUGHES INCORPORATED**
[US/US]; 3900 Essex Lane, Suite 1200, Houston, TX
77027 (US).

(72) Inventors: **BAUGH, John, L.**; 7519 Plumtree Forest
Court, Houston, TX 77095 (US). **GOMEZ, Leopoldo, S.**;
12002 Rhinebeck Dr., Houston, TX 77089 (US).

(74) Agents: **CARSON, Matt** et al.; 3900 Essex Lane, Suite
1200, Houston, TX 77027 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: COMPLIANT SWAGE



(57) Abstract: A compliant swage (A) has the ability to change shape to allow clearance of an obstruction while permitting expansion to go on in other areas removed from the obstruction. A series of segments (40, 42) move with respect to each other longitudinally to change overall size. The segments have an additional degree of freedom to change from a round profile of varying diameter to an oblong, elliptical, or an irregular shape so as to compensate in the portion that encounters an obstruction to let the swage pass while at the same time permitting the intended maximum expansion in other portions where conditions permit such expansion.

WO 2004/079157 A1

APPLICATION FOR PATENT

Title: Compliant Swage

Inventors: John L. Baugh and Leopoldo S. Gomez

FIELD OF THE INVENTION

[0001] The field of the invention is expansion of tubulars and more particularly the use of a compliant swage that can expand the tubular while compensating for tight spots where expansion cannot take place.

BACKGROUND OF THE INVENTION

[0002] Tubulars are expanded for a variety of reasons. In one application a patch is expanded to repair cracked casing. In other applications tubulars or liners are expanded to connect to each other or to casing downhole to present a larger cross-sectional area for a segment of the well. In other applications, deformation or a collapse of casing from forces of the surrounding formation needs to be corrected to improve the borehole cross-sectional area in the affected zone.

[0003] Swages have been used to accomplish this task. Swages are generally a tapered shape coming to a fixed maximum diameter such that when pushed or pulled through the obstructed area results in making the tubular either resume its initial round dimension or expand the tubular into an even larger round dimension. More recently swages that could change circular dimension were disclosed by the inventors of the present invention in a U.S. provisional application filing on February 11, 2002 having serial number 60/356,061. That design allowed connected segments to move longitudinally with respect to each other to vary the circular maximum diameter of the swage. This ability had the advantage of changing size in the face of an obstruction to avoid sticking the swage or overloading the swage driving apparatus. This device had the capability of reducing to a smaller diameter to allow clearing of an obstruction. Its limitation was that if a tight spot adjacent the outside of only a part of the circumference of the tubular to be expanded was encountered, the swage reduced its diameter symmetrically to clear the obstruction. This resulted in a decrease in cross-sectional area beyond the amount necessary to clear the localized obstruction.

[0004] The present invention presents a compliant swage that has enough range of motion among its components to provide sufficient articulation to let the swage go out of round in profile. This permits a part of the swage to reduce in dimension at the localized obstruction while in the remaining regions where there is no such resistance, the expansion can continue as the swage advances. The net result is a larger cross-sectional area can be obtained than with the prior design and the obstruction can still be cleared. These and other advantages of the present invention will become more apparent to those skilled in the art from a review of the description of the preferred embodiment and the claims, which appear below.

SUMMARY OF THE INVENTION

[0005] A compliant swage has the ability to change shape to allow clearance of an obstruction while permitting expansion to go on in other areas removed from the obstruction. A series of segments move with respect to each other longitudinally to change overall size. The segments have an additional degree of freedom to change from a round profile of varying diameter to an oblong, elliptical, or an irregular shape so as to compensate in the portion that encounters an obstruction to let the swage pass while at the same time permitting the intended maximum expansion in other portions where conditions permit such expansion.

DETAILED DESCRIPTION OF THE DRAWINGS

[0006] Figure 1 is a section view of the swage assembly in the run in position;

[0007] Figure 2 is the view of figure 1 in the beginning to swage position;

[0008] Figure 3 is a detail of a pair of segments that are upwardly oriented and an adjacent pair that is oppositely oriented;

[0009] Figure 4 is a section view through lines 2-2 of Figure 2;

[0010] Figure 5 is the view of Figure 2 showing the expansion proceeding prior to encountering an obstruction;

[0011] Figure 6 is the view of Figure 5 just as an obstruction is about to be encountered;

[0012] Figure 7 is a section view along lines 7-7 of Figure 2 when an obstruction is encountered;

[0013] Figure 8 is a perspective view of two adjacent segments showing how they connect to each other in a tongue and groove manner;

[0014] Figure 9 is the view from the opposite end as compared to Figure 8;

[0015] Figure 10 is a perspective view of the assembled segments in the maximum dimension position;

[0016] Figure 11 is the view of Figure 10 in the minimum dimension position during run in;

[0017] Figure 12 shows an alternative embodiment where the segments abut in arcuate contact and the segments are in a round configuration;

[0018] Figure 13 is the view of Figure 12 after an obstruction is encountered and the segments have moved to an out of round shape to clear the obstruction;

[0019] Figure 14 is an alternate embodiment to Figure 3 where a single segment is connected at the T-shaped connection instead of a pair of segments; and

[0020] Figure 15 is the mating segment to Figure 14 in the alternative embodiment to Figure 12 where the segments have arcuate edge contact and a single segment rather than a pair is connected at a T-shaped connection.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0021] Figure 1 shows the preferred embodiment of the swage apparatus A of the present invention. It has a mandrel 10 with thread 12 for connecting tubing or some other driving mechanism (not shown). Passage 14 has lateral exits 16 and 18 to communicate applied pressure to annular cavities 20 and 22 respectively. Rounding piston 24 is sealed by seals 26 and 28 so that pressure in cavity 20 urges rounding piston 24 toward lower end 30 of the apparatus A. Swage anchor 32 is held at thread 34 to mandrel 10. Near its lower end 36 there are a plurality of preferably T-shaped openings 38, although other shapes can be used.

[0022] Referring to Figure 3 swage segments **40** and **42** have C-shaped upper ends **44** and **46** respectively so that when brought together the adjacent upper ends **44** and **46** take on a T-shape that is designed to fit loosely in T-shaped openings **38** in swage anchor **32**. Referring to Figures 1 and 9, it can be seen that upper ends **44** and **46** respectively include beveled surfaces **48** and **50** onto which the beveled lower end **52** of swage anchor **32** is brought to bear.

[0023] The assembly that comprises the compliant swage **54** is partially shown in a flattened view in Figure 3 and in perspective in Figure 11, during the run in procedure.

[0024] Figure 11 shows a pattern of pairs of segments **40** and **42** that are attached to swage anchor **32** interspersed with segment pairs **56** and **58** that are attached below to the fixed diameter swage **60** through generally T-shaped openings **62**. Openings **62** are the mirror image of openings **38** and serve a similar function. Referring to Figure 1, the optional swage **60** is biased by preload piston **64**. Seals **66** and **68** seal piston **64** in cavity **22** so that pressure through passage **18** drives piston **64** and segment pairs **56** and **58** in an uphole direction toward thread **12**. That same pressure in passage **14** drives the rounding piston **24** downhole toward lower end **30** and into beveled surfaces **48** and **50** of each segment pair **40** and **42**. Force to move the rounding piston **24** may be provided by mechanical springs or other means. Rounding piston **24**, in the absence of an irregular obstruction downhole, forces the segments **40**, **42**, **56** and **58** into a circular shape shown in Figure 4, due to the contact between beveled surface **52** with its corresponding beveled surfaces **48** and **50** on segment pairs **40** and **42**. The swage **60** is optional and piston **64** can bear directly on segment pairs **56** and **58**, without departing from the invention. Alternatively, the bias provided hydraulically by piston **64** can be provided by other means such as mechanically by a spring or a stack of Belleville washers, for some examples. In some configurations all the required preload will be provided by the fixed swage **60**.

[0025] Figure 1 illustrates a run in position with preferably no pressure in passage **14**. In that case there is no uphole pressure from piston **64** and segment pairs **56** and **58** are in their lowermost position so that the compliant swage assembly is at its minimum dimension. This position is best seen in the perspective view of Figure 11. Ridgelines **70** and **72** on segment pairs **56** and **58** are longitudinally offset from

ridgelines **74** and **76** on segment pairs **40** and **42**. This should be compared with the swaging position shown in Figure 10. In this view, fluid pressure is applied in passage **14** pushing piston **64** uphole and with it segment pairs **56** and **58**. The ridgelines **70**, **72**, **74** and **76** align in a circular configuration, as shown in Figure 4. The circular configuration is promoted by the wedging action from beveled lower end **52** of rounding piston **24** forcing the segment pairs **40** and **42** into such a shape. Since all the segment pairs are interconnected, as will be described, the compliant swage assembly **54** as a whole assumes a circular shape for the purpose of swaging at the pre-designated maximum dimension, illustrated in the perspective view of Figure 10.

[0026] Figure 4 shows a mode of interconnection. Every segment preferably has a tongue **78** on one edge and a groove **80** on the opposite edge. On either side of each tongue **78** are surfaces **82** and **84**. On either side of groove **80** are surfaces **86** and **88**. Surfaces **84** and **88** define a gap **90** between them and surfaces **82** and **86** define a gap **92** between them. These gaps allow articulation between adjacent segments so that the circular shape shown in Figure 4 for swaging at maximum dimension uniformly until an exterior obstruction is met can change into an out of round shape shown in Figure 7. To assume the shape of Figure 7, some of the gaps **90** have closed completely while gaps **92** between the same two segments have opened fully in zones **94** and **96**. At the same time, in zones **98** and **100** the movement is opposite. The compliant swage assembly **54** has now taken a somewhat oval shape in departing from the optimal round shape. It should be noted that depending on the allowable dimensions of gaps **90** and **92** a greater or lesser amount of articulation is possible. There are several limiting factors on the amount of articulation provided. One is the strength of the connection between a tongue **78** and an adjacent groove **80**. Another, is the desire to keep the outer gaps **92** to a minimum dimension for the reason that large gaps can allow opposed edges such as **102** and **104** to concentrate stress in the expanded tubular by putting line scores in it. Depending on the amount of expansion and subsequent service, such scoring and stress concentration can result in premature cracking of the expanded tubular. Figures 4 and 7 illustrate that the articulated swage assembly **54** is held together at maximum dimension of Figure 4 or in an out of round articulated shape to allow the expansion of the tubular to the maximum dimension where no resistance is encountered while allowing inward articulation to clear the obstruction in the zone where it is encountered. The net result

is a larger expanded cross-section of the tubular where the obstruction occurs than would have been possible with the prior design that simply transitioned from a larger circle to a sufficiently smaller circle to clear the exterior obstruction. Another limiting issue on the amount of articulation is the tubular being expanded. There are limits that the tubular can endure in differential expansion between its various zones to clear an obstruction. The design of Figures 4 and 7 represent one solution to the need to hold the segments together while permitting articulation to achieve a desired swaging shape change. Clearly the tongue and groove connections hold the assembly of segments together as they are moved from the run in position of Figure 1 to the onset of swaging position shown in Figure 2 with pressure applied to passage 14.

[0027] Figures 12,13,14 and 15 show an alternate design. The segments are no longer in pairs as shown in Figure 3; rather a segment 110 has a T-shaped connection 108 to be inserted into an opening 38 in swage anchor 32. Abutting on either side is a segment 106 that is oppositely oriented and connected to swage 60. The interface between the segments 106 and 110 is no longer a tongue and groove. Rather, each interface is a pair of arcuate surfaces 112 and 114 to allow the assembly articulate from the originally round shape shown in Figure 12 to an out of round shape shown in Figure 13 to clear an obstruction external to the tubular being expanded. The end connections of the segments 106 and 110 respectively to swage anchor 32 and swage 60 are made deliberately loose to permit relative movement between surfaces 112 and 114 to permit the articulation to the desired shape to avoid the obstruction exterior to the tubular being swaged. One notable difference is that there are no gaps in the periphery 116 where the swaging action is taking place regardless of the configuration of the segments in the round or out of round positions shown in Figures 12 and 13. Those skilled in the art will appreciate that band springs or equivalents can be used to limit the outward movement of the segments 106 and 110 as the interacting arcuate surfaces 112 and 114 do not provide such an outward travel stop. Even using the interface of Figures 12 and 13, the minimum and maximum dimensions of the compliant swage assembly 54 shown in Figures 1 and 2 are still achieved by relative longitudinal movement between the segments oriented uphole and those that are oppositely oriented. The total number of segments is fewer in the Figures 12,13,14 and 15 version but greater numbers of segments can also be used. For example, segment pairs as shown in Figure 3 can be used with the arcuate edge interfaces,

within the scope of the invention. Conversely, as shown in Figure 14 the segment pairs of Figure 3 can be cut in half using larger segments that still employ an edge connection using a tongue and groove or another mechanically equivalent arrangement.

[0028] The method of using any of the above-described configurations can be seen by initially looking at Figure 1 for the run in position. At this time there is no pressure applied in passage 14 and the piston 64 and with it the swage 60 and the connected segments, such as 56 and 58 are in their lowermost position, simply due to their own weight. The compliant swage assembly 54 is in the Figure 11 position with ridgelines 70 and 72 out of alignment with ridgelines 74 and 76. The compliant swage 54 is therefore in its minimum diameter position. Those skilled in the art will realize that the expansion can occur along the aligned ridge lines, as shown in Figure 10 or along a surface as opposed to a line contact shown in Figure 10. The Figure 10 position is achieved by putting pressure from the surface in passage 14 to push swage 60 uphole and to force rounding piston 24 down on beveled surfaces 48 and 50. This latter action puts the compliant swage in a round configuration illustrated in Figure 4 for the start of swaging. This position of the apparatus A is shown in Figure 2. If used, the fixed swage 60 enters the tubing to be expanded first. If it will not pass, the apparatus A must be retrieved. Once it passes, the compliant swage assembly 54, now in the Figure 10 position due to pressure in passage 14, makes contact with the tubular to be expanded. The segments remain in the round position shown in Figure 4 as long as there is no external obstruction to expansion of the tubular, as is shown in Figure 5. When a restriction or obstruction is reached, as shown in Figure 6, the compliant swage assembly 54 will articulate to change dimension to try to pass the obstruction by getting smaller in the zone where the obstruction is found and swaging as large as possible where the obstruction is not present. This articulation occurs with pressure continuing to be applied in passage 14. If the tongue 78 of one segment is engaged to a groove 80 in an adjacent segment, relative rotation about an axis defined by the tongue in groove connection permits the articulation as the size of gaps 90 and 92 between the affected segment pairs begins to change. In the abutting arcuate surfaces design shown in two positions in Figures 12 and 13, relative rotations along the arcuate surfaces 112 and 114 results in the desired articulation while presenting a continuous and uninterrupted surface or edge 116 for continued swaging despite an

obstruction. In the end, if the compliant swage assembly **54** can actually pass through the obstruction, the resulting cross-sectional area of the expanded tubular is larger than it otherwise would have been if its circular cross-section had been maintained but its dimension reduced to the point where the obstruction could have been cleared. Clearly the larger the number of segments in the compliant swage assembly **54** the better its ability to articulate. However, the maximum round diameter of the compliant swage assembly **54** and the required strength of the segments to actually do the swaging required will have an effect on the number of segments to be employed.

[0029] Those skilled in the art will appreciate that surfaces **112** and **114** do not have to be singular arcs or have the same radius. They can be a series of surfaces and have different curvatures. The illustrated embodiment is illustrative of the inventive concept of articulation in combination with nearly continuous edge or surface contact. The alternative articulation concept is also illustrative of the ability to articulate but allowing some gaps in the swaging line or surface contact to accomplish the desired articulation.

[0030] The foregoing disclosure and description of the invention are illustrative and explanatory thereof, and various changes in the size, shape and materials, as well as in the details of the illustrated construction, may be made without departing from the spirit of the invention.

We claim:

1. An adjustable swage for use on a downhole tubular, comprising:
a rounded body mounted to a mandrel wherein said body is movable into a plurality of positions to create a variety of profiles effective for a full 360° about said mandrel.
2. The swage of claim 1, wherein:
said profiles comprise circular and non-circular shapes.
3. The swage of claim 1, wherein:
said round body comprises a plurality of articulated components that allow the profile to be reduced in response to a portion of the tubular that resists expansion while permitting a larger profile dimension in other parts of the tubular where there is no such resistance.
4. The swage of claim 3, wherein:
said articulated components present no gaps along said profile.
5. The swage of claim 3, wherein:
said articulated components present gaps along said profile.
6. The swage of claim 3, wherein:
said articulated components move relatively to each other to change the dimension on at least a portion of said profile.
7. The swage of claim 6, wherein:
said articulated components rotate on adjacent edge arcuate surfaces.
8. The swage of claim 7, further comprising:
a retention device mounted around said articulated components to hold them together.
9. The swage of claim 6, wherein:

said articulated components are retained to each other within said profile.

10. The swage of claim 9, wherein:

pairs of said articulated components are retained to each other by a tongue and groove connection.

11. The swage of claim 10, wherein:

said tongue and grove connection has a longitudinal axis whereupon adjacent articulated components that are secured by said tongue and groove connection can rotate with respect to each other about said longitudinal axis of said tongue and groove joint.

12. The swage of claim 11, wherein:

gaps along said profile close to reduce its dimension to clear an obstruction while gaps widen to increase said profile in other location to achieve, in other zones where there is insufficient resistance, the desired expansion of the tubular.

13. The swage of claim 1, wherein:

said body is formed of a plurality of abutting segments movable with respect to each other.

14. The swage of claim 13, wherein:

said segments each comprise a high location and at least some of said segments are movable to selectively align said high locations to obtain a maximum diameter or to offset them to attain a minimum diameter.

15. The swage of claim 13, wherein:

said mandrel has a longitudinal axis and said segments slide relatively to each other in the direction of said longitudinal axis.

16. The swage of claim 15, wherein:

said segments are retained to each other while moving relatively to each other in a longitudinal direction.

17. The swage of claim **16**,wherein:

said segments are retained to each other at their abutting edges by a tongue and groove connection.

18. The swage of claim **13**,wherein:

said segments are wedge shaped having a narrow end and a wide end and are arranged in an alternating pattern where the narrow end of one segment, in a first orientation, is adjacent the wide end of a neighboring segment, in a second orientation, on either side.

19. The swage of claim **18**,wherein:

said segments in one of said first and second orientations is selectively held fixed and said segments in the other of said first and second orientations is movable.

20. The swage of claim **19**,wherein:

said segments each comprise a high location and at least some of said segments are movable to selectively align said high locations to obtain a maximum diameter or to offset them to attain a minimum diameter.

21. The swage of claim **20**,wherein:

said movable segments are biased in the direction to obtain said maximum diameter.

22. The swage of claim **21**,wherein:

said movable segments are driven as well as biased in the direction to obtain said maximum diameter.

23. The swage of claim **22**,wherein:

said movement of said movable segments toward said maximum diameter is in conjunction with a ratchet which prevents said movable segments from movement in a reversed direction.

24. The swage of claim **23**, wherein:

said segments that are held fixed are secured to a ring, whereupon relative rotation between said ring and said mandrel moves said segments formerly held fixed away from said movable segments to allow said body to move toward said minimum diameter.

25. The swage of claim **22**, wherein:

said movable segments are driven by a piston driven by fluid pressure applied to it through said mandrel; and

said bias is provided by a stack of Belleville washers.

26. The swage of claim **20**, wherein:

said mandrel has a longitudinal axis and said segments slide relatively to each other in the direction of said longitudinal axis.

27. The swage of claim **26**, wherein:

said segments are retained to each other while moving relatively to each other in a longitudinal direction.

28. The swage of claim **27**, wherein:

said segments are retained to each other at their abutting edges by a tongue and groove connection.




FIG. 1

2/13




FIG. 2

3/13




FIG. 3




FIG. 4

SUBSTITUTE SHEET (RULE 26)

4/13




FIG. 5

5/13





FIG. 6

6/13

**FIG. 7**

7/13




FIG. 8

8/13




FIG. 9

9/13




FIG. 10




FIG. 11




FIG. 13




FIG. 12

12/13




FIG. 14

13/13




FIG. 15

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US2004/002905

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 E21B43/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E21B B21D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 450 261 B1 (BAUGH JOHN L) 17 September 2002 (2002-09-17) The subject-matter of claims 7-12 and 15-17 are considered obvious. column 2, line 5 - line 8 column 2, line 23 - line 43; figure 2 ----	1-17
X	US 2002/185274 A1 (SIMPSON NEIL A A ET AL) 12 December 2002 (2002-12-12) paragraph '0025!; figures 2,3 ----	1
A,P	WO 03/069115 A (BAKER HUGHES INC) 21 August 2003 (2003-08-21) cited in the application page 3, line 14 -page 4, line 29 -----	1-28



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

28 June 2004

Date of mailing of the international search report

06/07/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Stroemmen, H.

INTERNATIONAL SEARCH REPORT
information on patent family members

International Application No
PCT/US2004/002905

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6450261	B1	17-09-2002	AU 7734401 A	11-04-2002
			CA 2358312 A1	10-04-2002
			GB 2367842 A , B	17-04-2002
			NO 20014909 A	11-04-2002
US 2002185274	A1	12-12-2002	US 2001045284 A1	29-11-2001
			US 6325148 B1	04-12-2001
			US 2001040054 A1	15-11-2001
			US 2002079100 A1	27-06-2002
			AU 772790 B2	06-05-2004
			AU 1044201 A	03-07-2001
			CA 2393744 A1	28-06-2001
			EP 1242714 A1	25-09-2002
			WO 0146551 A1	28-06-2001
			NO 20022786 A	14-08-2002
			US 2003106698 A1	12-06-2003
			US 2003188868 A1	09-10-2003
			US 6598678 B1	29-07-2003
			US 2002166664 A1	14-11-2002
			US 2003019638 A1	30-01-2003
			AU 5493101 A	20-11-2001
			CA 2406663 A1	15-11-2001
			EP 1278932 A1	29-01-2003
			WO 0186111 A1	15-11-2001
			NO 20024946 A	23-12-2002
WO 03069115	A	21-08-2003	WO 03069115 A2	21-08-2003
			US 2003155118 A1	21-08-2003